

Noxudol Body

Fast drying abrasion protection

General

Noxudol Body is a fast drying, gum- and alkyd-based rust protecting compound with very good adhesion.

Noxudol Body is resistant to salt and other frequently occurring road chemicals and furthermore resistant to degreasing agents.

Range of application

Noxudol Body is especially suitable for visible parts, i.e. front-panels and door sill boxes as well as primer for the treatment of damage caused by flying stones and similar minor rust damages.

Noxudol Body gives a matte finish that can be retained or painted over.

Instructions for use

Make sure that the surface is dry and free from oil, dirt and rust.

Use a primer on bare steel surfaces before application. Mask and cover all parts that are not going to be sprayed. Protect the floor. Shake the bottle vigorously for 1 minute and apply a thin and even layer from a distance of 25-30 cm at a temperature of min. 15 °C. Repeat 1-2 times and let it set for 10 minutes.

To avoid clogging of the spray tip after use turn the tin upside down and spray for some seconds until only gas escapes through the valve.

Package

32011310 / 500 ml spray (12 pieces / pack.)
32011421 / 1-lit can (12 pieces / pack.)

Technical data

Colour:	Black
Consistency:	Thick liquid sprayable
Type of film:	Alkyd resin / polymer
Density at 20° C	1000 ± 40 kg/m ³
Solvents:	Naphta
Film thickness:	100 - 250 µm
Application temperature:	15 - 25° C
Removal with:	White spirit
Dilution:	White spirit
Storing time:	12 months
Storing temperature:	Store in a cool place

For further information we recommend the safety data sheet or instruction on package.

Issue: 2014-01-17



Auson AB, Kungsbacka, Sweden
T: +46 (0)300-56 20 00
www.auson.se

Dessa anvisningar och information är avsedda att vägleda förbrukaren vid användning av produkten och lämnas utan förbindelse. Vid oklarhet tillråds egna prov eller skriftliga råd från oss.

Noxudol